



The function of **AHD** wiper is to scrape heavily adhering particles off the cylinder rod. It should always be used in combination with a second wiper in elastomer or PU.

This combination is very suitable for heavy duty applications in earthmoving and mining equipment.

The wiper is produced in polyamide (PA) or acetal resin (POM) which have a **high resistance to abrasion**.

Operating conditions

Temperature -40°C to 100°C
Speed ≤ 0,8 m/s

Materials

Polyamid POM or PA

Assembly

The wipers may easily be clipped into the grooved housing

Advantages

- Easy to assemble
- Good price-performance ratio
- Good abrasion resistance
- For heavy duty applications (excavators...)
- Very small housing

Please contact us for applications approaching maximum values.

d	D	L	C	Reference
44,5	56	2	55	AHD-44
45	56	2,1	55	AHD-45
56	67	2,1	66	AHD-56
59,5	71	2	70	AHD-59
63	74	2,1	73	AHD-63
69,5	81	2	80	AHD-69
70	82	2,1	81	AHD-70
75	87	2,1	86	AHD-75
78	89,5	2	88,5	AHD-78
80	92	2,1	91	AHD-80
87	98,5	2	97,5	AHD-87
90	102	2,1	101	AHD-90
97	108,5	2	107,5	AHD-97
100	112	2,1	111	AHD-100
104	115,5	2	114,9	AHD-104
110	122	2,1	121	AHD-110
118	129,5	2	128,5	AHD-118
120	132	2,1	131	AHD-120
124	136	2,1	135	AHD-124
130	150	2,6	148,6	AHD-130
140	160	2,6	158,6	AHD-140
150	170	2,6	168,6	AHD-150
160	180	2,6	178,6	AHD-160
180	200	2,6	198,6	AHD-180
200	220	2,6	219,6	AHD-200