



The function of **ANV** wiper is to prevent introduction of contamination into the system, to protect the guiding parts and to extend the service life of the rod seal. The wiper lip produces an effective cleaning action to avoid damage to all internal components.

The sealing lip on the static side **stops the intrusion of impurities** and moisture via the outer diameter even before entering the groove. The ribs on the inner surface give stability and prevent twisting of the wiper in the groove or sticking onto the rod.

This wiper is produced in polyurethane which ensures increased **wear resistance** and an extended service life due to good resistance against weathering.

**Operating conditions**

Temperature -30°C to 100°C  
 Speed ≤ 1 m/s

**Materials**

Polyurethane

**Assembly**

The wipers may easily be mounted into the grooved housing

**Advantages**

- Very good protection of the housing against external intrusion and moisture
- No tilting or twisting in the groove
- Excellent abrasion resistance
- Extended service life
- Easy to assemble
- Most housings in accordance to ISO 6195/A
- Simple groove construction

**Please contact us for applications approaching maximum values.**

d	D	L	C	L1	H	Reference
16	24	5	21,5	7	7,8	ANV-16
18	26	5	23,5	7	7,8	ANV-18
20	28	5	25,5	7	7,8	ANV-20
	28	4	26	6	6,7	ANV-20-1
22	30	5	27,5	7	7,8	ANV-22
	30	4	28	6	6,7	ANV-22-1
25	33	5	30,5	7	7,8	ANV-25
	33	4	31	6	6,7	ANV-25-1
28	36	5	33,5	7	7,8	ANV-28
	36	4	34	6	6,7	ANV-28-1
30	38	4	36	6	6,7	ANV-30
32	40	5	37,5	7	7,8	ANV-32
	40	4	38	6	6,7	ANV-32-1
35	43	4	41	6	6,7	ANV-35
36	44	5	41,5	7	7,8	ANV-36
	44	4	42	6	6,7	ANV-36-1
40	48	5	45,5	7	7,8	ANV-40
	48	4	46	6	6,7	ANV-40-1
45	53	5	50,5	7	7,8	ANV-45
	53	4	51	6	6,7	ANV-45-1
50	58	5	55,5	7	7,8	ANV-50
	58	4	56	6	6,7	ANV-50-1
55	63	4	61	6	6,7	ANV-55-1
	65	6,3	62	8,3	9	ANV-55
56	66	6,3	63	8,3	9	ANV-56

d	D	L	C	L1	H	Reference
60	68	5	65,5	7	7,8	ANV-60-2
	68	4	66	6	6,7	ANV-60
	68	5	65,5	7	7,8	ANV-60-2
	70	6,3	67	8,3	9	ANV-60-3
	72	5,5	69	7	10	ANV-60-1
63	73	6,3	70	8,3	9	ANV-63
70	78	4	76	6	6,7	ANV-70-1
	80	6,3	77	8,3	9	ANV-70
	82	5,5	79	7	10	ANV-70-2
75	83	4	81	6	6,7	ANV-75
80	88	4	86	6	6,7	ANV-80-1
	90	6,3	87	8,3	9	ANV-80
	92	5,5	89	7	10	ANV-80-2
85	95	6,3	92	8,3	10	ANV-85
90	98	4	96	6	6,7	ANV-90-1
	100	6,3	97	8,3	9	ANV-90
	102	5,5	99	7	10	ANV-90-2
100	115	9,5	110	12	13	ANV-100
110	125	9,5	120	12	13	ANV-110
115	127	5,5	124	7	10	ANV-115
125	140	9,5	135	12	13	ANV-125
140	155	9,5	150	12	13	ANV-140
150	165	9,5	160	12	13	ANV-150
160	175	9,5	170	12	13	ANV-160
180	195	9,5	190	12	13	ANV-180
200	215	9,5	210	12	13	ANV-200