



SDC single acting rod seal can be used in hydraulic or pneumatic cylinders. This NBR profile is designed with a shorter inner sealing lip which ensures **low friction**.

Operating conditions

Pressure $\leq 12 \text{ MPa}$
 Temperature $-30^\circ\text{C to } 100^\circ\text{C}$
 Speed $\leq 0,5 \text{ m/s}$

Materials

NBR 80 Sh A

Assembly

In closed grooves

Advantages

- Easy installation
- Low friction
- Good price-performance ratio
- Compact housing

Please contact us for applications approaching maximum values.

d	D	L	Reference
4	9	4	SDC-0409
	10	4,7	SDC-0410
6	10	3,5	SDC-0610
8	14	4,5	SDC-0814
9	14	4	SDC-0914
10	13,6	2,7	SDC-1013
	15	4	SDC-1015
	16	5	SDC-1016
12	18,5	5	SDC-1218
16	22,5	5	SDC-1622
	24	6	SDC-1624
19	25	5,5	SDC-1925
20	28	6	SDC-2028
22	30	6	SDC-2230
25	33	6	SDC-2533
28	36	6	SDC-2836
30	40	7,5	SDC-3040

d	D	L	Reference
32	42	7,5	SDC-3242
35	45	7,5	SDC-3545
36	46	7,5	SDC-3646
40	50	7,5	SDC-4050
45	55	7,5	SDC-4555
50	60	7,5	SDC-5060
56	66	7,5	SDC-5666
60	72	9,5	SDC-6072
63	75	9,5	SDC-6375
70	82	9,5	SDC-7082
80	92	9,5	SDC-8092
90	102	9,5	SDC-90102
95	107	9,5	SDC-95107
100	115	11	SDC-100115
130	145	11	SDC-130145